

### Attachment D.3 Price Sheet: Dump Trucks

Please see Attachment D: Instruction and General Information for Instructions, Color Key, and Reference Key.

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Please fill in the cells in yellow and soft yellow located in the columns below for the Representative Models your company bids on.

Attachment D.3 Price Sheet: Dump Trucks					Please fill in the cells in yellow and soft yellow located in the columns below for the Representative Models your company bids on.								
Please see Attachment D: Instruction and General Information for Instructions, Color Key, and Reference Key.					Bidder Name: <sup>7</sup>		<Insert Bidder Name>						
Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.													
Group <sup>1</sup>	Contract Code <sup>2</sup>	Base Vehicle Description <sup>3</sup>	GVWR <sup>4</sup> (lbs.)	Payload Capacity (approx. lbs.) <sup>5</sup>	Accepted Brands <sup>6</sup>	Manufacturer/Brand <sup>8</sup>	Representative Model <sup>9</sup>	Representative Model Number <sup>10</sup>	Base Vehicle Price (\$###,###.00) <sup>11</sup>	OEM Options Discount (\$#%) <sup>12</sup>	Calculated Score <sup>13</sup>	Customer Pick Up Discount (\$###,###.00) <sup>14</sup>	Estimated Lead time in Days (###) <sup>15</sup>
DUMP TRUCK	310	4 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 28,000 LBS. GVWR (4x2)	28,000	13,850	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL 4000-SERIES, OR APPROVED EQUIVALENT						\$ -		
	320	5 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 33,000 LBS. GVWR (4x2)	33,000	18,200	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL 4000-SERIES, OR APPROVED EQUIVALENT						\$ -		
	330	4 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 28,000 LBS. GVWR (4x2)	28,000	12,950	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL 4000-SERIES OR APPROVED EQUIVALENT						\$ -		
	340	5 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 33,000 LBS. GVWR (4x2)	33,000	17,350	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL 4000-SERIES OR APPROVED EQUIVALENT						\$ -		
	350	8 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)	52,000	30,550	FREIGHTLINER M2, INTERNATIONAL 4000/7000-SERIES, OR APPROVED EQUIVALENT						\$ -		
	360	8 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)	52,000	30,550	FREIGHTLINER M2, INTERNATIONAL 4000/7000-SERIES, OR APPROVED EQUIVALENT						\$ -		
	370	12 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)	64,000	41,800	FREIGHTLINER M2, INTERNATIONAL 7000-SERIES, MACK GRANITE, OR APPROVED EQUIVALENT						\$ -		
	380	12 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)	64,000	41,800	FREIGHTLINER M2, INTERNATIONAL 7000-SERIES, OR APPROVED EQUIVALENT						\$ -		

GROUP 3, NO. 25101601-310: 4 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 28,000 LBS. GVWR (4x2)								
GVWR* (lbs.) <sup>4</sup>	28,000		Payload Capacity (approx. lbs.) <sup>5</sup>	13,850				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE IS RECOMMENDED TO TRANSPORT UP TO THREE (3) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
ENGINE:	10	A.	Diesel engine, 5.9L, 210 Gross HP (per the latest issue of SAE J1349) and 520 lbs.-ft. Gross Torque, minimum.	State Liters.				
				State Gross HP.				
				State Gross Torque.				
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	State Engine/Emissions Type.				
				State Urea Tank Size (in gallons), if required.				
		C.	Standard cooling system with antifreeze.					
		D.	Dry type air cleaner with service (restriction) indicator.					
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.					
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.					
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.					
TRANSMISSION:	20	A.	Automatic transmission, five (5)-speed minimum, with provisions for a PTO. Allison 2500RDS, or Approved Equivalent.					
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	State Manufacturer.	State Model No.			
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 9,000 lbs. capacity.					
		B.	Front shock absorbers.					
		C.	Front wheel oil-lubricated bearings and seals.					
		D.	Single speed rear axle and suspension, minimum 19,000 lbs. capacity. Rear axle ratio is to be a 5.57/5.71 for 2400 RPM engines, 5.57/5.71/5.86/5.88 for 2500 RPM engines, 6.14/6.43/6.50 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH.	State Rear Suspension Capacity (lbs.).	State Rear Axle Ratio.	State Engine RPM.	State Top Speed (MPH).	
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.					
		F.	Auxiliary rear leaf spring(s) or rubber helper.					
		G.	"No-Spin" or driver control traction differential (DCDL) on rear axle.					
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.					
		B.	Power steering.					

**GROUP 3, NO. 25101601-310: 4 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 28,000 LBS. GVWR (4x2)**

<b>GVWR* (lbs.)<sup>4</sup></b>	<b>28,000</b>	<b>Payload Capacity (approx. lbs.)<sup>5</sup></b>	<b>13,850</b>
<b>Intended Use:</b>	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE IS RECOMMENDED TO TRANSPORT UP TO THREE (3) INDIVIDUALS.		
<b>Bidder Name:<sup>7</sup></b>	<Insert Bidder Name>	<b>Representative Model:<sup>9</sup></b>	<b>Rep. Model Number:<sup>10</sup></b>
		0	0
		<b>BV Price:<sup>11</sup></b>	<b>OEM Options Discount:<sup>13</sup></b>
		\$ -	0.0%

**Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.**

Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
<b>COMFORT ITEMS:</b>	50	A.	Factory installed AM-FM stereo radio with two speakers and antenna.					
		B.	Air conditioner with integral heater and defroster.					
		C.	Arm rests both sides, if available; sun visors, both sides.					
		D.	Tinted glass all windows, including windshield.					
<b>SAFETY ITEMS:</b>	60	A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.					
		B.	Standard electric horn.					
		C.	Outside mirrors, left and right side. Mirrors to be six (6) x twelve (12) inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.					
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.					
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed.					
			<b>NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.</b>					
		F.	All access steps shall be self-cleaning slip-resistant grating.					
<b>BRAKES:</b>	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.					
		B.	Spring applied parking brake.					
		C.	Front and rear automatic slack adjusters.					
		D.	Front and rear dust shields.					
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)					
		F.	Low air pressure warning indicator.					
		G.	<b>Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.</b>	<b>State Air Dryer with Heater Type.</b>				
<b>TIRES &amp; WHEELS:</b>	70	A.	Six (6) 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.					
		B.	All wheels to be one-piece steel disc, ten (10)-hole, I.S.O. hub pilot mount, 22.5 inch diameter.					
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.					
<b>CHASSIS, FRAME, CAB:</b>	80	A.	<b>Minimum 28,000 lbs. GVWR, factory certified.</b>	<b>State GVWR lbs.</b>				
		B.	<b>Minimum 859,000 in-lbs. RBM frame.</b>	<b>State Frame RBM in lbs.</b>				
		C.	<b>Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of three (3) to five (5) inches.</b>	<b>State Cab/Body (CB) Clearance.</b>				
		D.	<b>Factory installed fuel tank(s), minimum 70 U.S. gallons.</b>	<b>State Fuel Tanks(s) Capacity.</b>				
		E.	Front tow hooks or tow pins.					
		F.	Standard front bumper.					

GROUP 3, NO. 25101601-310: 4 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 28,000 LBS. GVWR (4x2)								
GVWR* (lbs.) <sup>4</sup>	28,000		Payload Capacity (approx. lbs.) <sup>5</sup>	13,850				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE IS RECOMMENDED TO TRANSPORT UP TO THREE (3) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.					
		B.	Full-width bench seat or individual driver seat with two (2)-man passenger seat.					
		C.	Grab handle(s) for cab entry, located at each entry door.					
		D.	Manufacturer's standard paint and colors.					
		E.	Rear cab window with fixed tinted glass.					
BODY:	84	A.	Four (4) cu. yd. dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-4 section 3.2.1.	State Body Manufacturer.				
				State Body Model No.				
				State Hoist Manufacturer.				
				State Hoist Model No.				
		B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.					
		C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.					
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Custom/ Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.					
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.					
		C.	Paint numbers are referenced only to identify colors.					
OPTIONS:	2004	A.	Manual transmission, six (6)-speed minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 9.01:1. Rear axle ratio shall be a 4.10/4.11 for 2400 RPM engines, 4.30/4.33 for 2500 RPM engines, 4.78/4.88 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant.	State Rear Axle Ratio.				(Credit)
				State Engine RPM.				
				State Top Speed (MPH).				
	3002	A.	Manufacturer's standard four-by-four (4x4) drive system model in lieu of base equipment four-by-two (4x2) model. Note: Provide only the difference in price between the two wheel drive model and the manufacturer's standard four-by-four (4x4) model offered.					(Credit)
5001	A.	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.						

GROUP 3, NO. 25101601-310: 4 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 28,000 LBS. GVWR (4x2)							
GVWR* (lbs.) <sup>4</sup>	28,000		Payload Capacity (approx. lbs.) <sup>5</sup>	13,850			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE IS RECOMMENDED TO TRANSPORT UP TO THREE (3) INDIVIDUALS.						
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>	
			0	0	\$ -	0.0%	
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>							
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>		
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>
	6001	A.	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately thirty-six (36) inches in length located on the left and right front corners of the vehicle.)				
	6201	A.	Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable. See section 3.2.				
	7001	A.	Tubeless radial tires with on/off highway tread for rear only. Bid four (4) 11R22.5G (14PR) or larger tires for on/off highway use and two (2) 11R22.5G (14PR) or larger tires for highway use. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	State Front Tire Code.			
				State Rear Tire Code.			
	8001	A.	Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than fourteen (14) inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.				
	8002	A.	Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.				
	8201	A.	Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).				
	8202	A.	Two-tone colors. Manufacturer's standard two-tone colors.				
	8401	A.	Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 2000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.				

GROUP 3, NO. 25101601-320: 5 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 33,000 LBS. GVWR (4x2)							
GVWR* (lbs.) <sup>4</sup>	33,000		Payload Capacity (approx. lbs.) <sup>5</sup>	18,200			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE IS RECOMMENDED TO TRANSPORT UP TO THREE (3) INDIVIDUALS.						
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>	
			0	0	\$ -	0.0%	
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>							
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>		
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>
ENGINE:	10	A.	Diesel engine, 5.9L, 210 Gross HP (per the latest issue of SAE J1349) and 560 lbs.-ft. Gross Torque, minimum.	State Liters.			
				State Gross HP.			
				State Gross Torque.			
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	State Engine/Emissions Type.			
				State Urea Tank Size (in gallons), if required.			
		C.	Standard cooling system with antifreeze.				
		D.	Dry type air cleaner with service (restriction) indicator.				
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.				
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.				
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.				
TRANSMISSION:	20	A.	Automatic transmission, six (6)-speed minimum, (International may bid a five (5)-speed, if required for the engine bid) with provisions for a PTO. Allison 3500RDS, or Approved Equivalent.				
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	State Manufacturer.			
				State Model No.			
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 12,000 lbs. capacity.				
		B.	Front shock absorbers.				
		C.	Front wheel oil-lubricated bearings and seals.				
		D.	Single speed rear axle and suspension, minimum 21,000 lbs. capacity. Rear axle ratio is to be a 6.14/6.43/6.50 for 2400 RPM engines, 6.50/6.83/6.86 for 2500 RPM engines, 6.43/6.50 for a 2800 RPM engines, (International - 6.14/6.17 for a 2600 RPM engine), or the closest possible ratio available that will provide a top speed of approximately 65 MPH.	State Rear Suspension Capacity (lbs.).			
				State Rear Axle Ratio.			
				State Engine RPM.			
				State Top Speed (MPH).			
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.				
		F.	Auxiliary rear leaf spring(s) or rubber helper.				
		G.	"No-Spin" or driver control traction differential (DCDL) on rear axle.				
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.				
		B.	Power steering.				

GROUP 3, NO. 25101601-320: 5 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 33,000 LBS. GVWR (4x2)								
GVWR* (lbs.) <sup>4</sup>	33,000		Payload Capacity (approx. lbs.) <sup>5</sup>	18,200				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE IS RECOMMENDED TO TRANSPORT UP TO THREE (3) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with two speakers and antenna.					
		B.	Air conditioner with integral heater and defroster.					
		C.	Arm rests both sides, if available; sun visors, both sides.					
		D.	Tinted glass all windows, including windshield.					
SAFETY ITEMS:	60	A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.					
		B.	Standard electric horn.					
		C.	Outside mirrors, left and right side. Mirrors to be six (6) x twelve (12) inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.					
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.					
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. <b>NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.</b>					
		F.	All access steps shall be self-cleaning slip-resistant grating.					
		G.	Daytime running lights.					
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.					
		B.	Spring applied parking brake.					
		C.	Front and rear automatic slack adjusters.					
		D.	Front and rear dust shields.					
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)					
		F.	Low air pressure warning indicator.					
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	State Air Dryer with Heater Type.				
TIRES & WHEELS:	70	A.	Six (6) 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.					
		B.	All wheels to be one-piece steel disc, ten (10)-hole, I.S.O. hub pilot mount, 22.5 inch diameter.					
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.					
CHASSIS, FRAME, CAB:	80	A.	Minimum 33,000 lbs. GVWR, factory certified.	State GVWR lbs.				
		B.	Minimum 1,700,000 in-lbs. RBM frame.	State Frame RBM in lbs.				
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of three (3) to five (5) inches.	State Cab/Body (CB) Clearance.				
		D.	Factory installed fuel tank(s), minimum 70 U.S. gallons.	State Fuel Tanks(s) Capacity.				
		E.	Front tow hooks or tow pins.					
		F.	Standard front bumper.					

GROUP 3, NO. 25101601-320: 5 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 33,000 LBS. GVWR (4x2)								
GVWR* (lbs.) <sup>4</sup>	33,000		Payload Capacity (approx. lbs.) <sup>5</sup>	18,200				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE IS RECOMMENDED TO TRANSPORT UP TO THREE (3) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.					
		B.	Full-width bench seat or individual driver seat with two (2)-man passenger seat.					
		C.	Grab handle(s) for cab entry, located at each entry door.					
		D.	Manufacturer's standard paint and colors.					
		E.	Rear cab window with fixed tinted glass.					
BODY:	84	A.	Five (5) cu. yd. dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-5 section 3.2.1.	State Body Manufacturer.				
				State Body Model No.				
				State Hoist Manufacturer.				
				State Hoist Model No.				
				State Tarp Manufacturer.				
				State Tarp Model No.				
		B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.					
		C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.					
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Customer/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.					
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.					
		C.	Paint numbers are referenced only to identify colors.					
OPTIONS:	2004	A.	Manual transmission, six (6)-speed minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 9.01:1. Rear axle ratio shall be a 4.10/4.11 for 2400 RPM engines, 4.30/4.33 for 2500 RPM engines, 4.88/4.89 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant.	State Rear Axle Ratio.				
				State Engine RPM.				
				State Top Speed (MPH).				
3002	A.	Manufacturer's standard four-by-four (4x4) drive system model in lieu of base equipment four-by-two (4x2) model. Note: Provide only the difference in price between the two wheel drive model and the manufacturer's standard four-by-four (4x4) model offered.				(Credit)		
5001	A.	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.						



**GROUP 3, NO. 25101601-320: 5 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 33,000 LBS. GVWR (4x2)**

<b>GVWR* (lbs.)<sup>4</sup></b>	<b>33,000</b>	<b>Payload Capacity (approx. lbs.)<sup>5</sup></b>	<b>18,200</b>
<b>Intended Use:</b>	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE IS RECOMMENDED TO TRANSPORT UP TO THREE (3) INDIVIDUALS.		
<b>Bidder Name:<sup>7</sup></b>	<Insert Bidder Name>	<b>Representative Model:<sup>9</sup></b>	<b>Rep. Model Number:<sup>10</sup></b>
		0	0
			<b>BV Price:<sup>11</sup></b>
			\$ -
			<b>OEM Options Discount:<sup>13</sup></b>
			0.0%

**Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.**

Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
	6001	A.	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately thirty-six (36) inches in length located on the left and right front corners of the vehicle.)					
	6201	A.	Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable. See section 3.2.					
	7001	A.	Tubeless radial tires with on/off highway tread for rear only. Bid four (4) 11R22.5G (14PR) or larger tires for on/off highway use and two (2) 11R22.5G (14PR) or larger tires for highway use. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	State Front Tire Code.				
				State Rear Tire Code.				
	8001	A.	Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than fourteen (14) inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.					
	8002	A.	Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.					
	8201	A.	Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).					
	8202	A.	Two-tone colors. Manufacturer's standard two-tone colors.					
	8401	A.	Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 2000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.					

GROUP 3, NO. 25101601-330: 4 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 28,000 LBS. GVWR (4x2)								
GVWR* (lbs.) <sup>4</sup>	28,000		Payload Capacity (approx. lbs.) <sup>5</sup>	12,950				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE HAS FOUR (4) FULL SIZE DOORS AND IS RECOMMENDED TO TRANSPORT FOUR (4) TO SIX (6) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
ENGINE:	10	A.	Diesel engine, 5.9L, 210 Gross HP (per the latest issue of SAE J1349) and 520 lbs.-ft. Gross Torque, minimum.	State Liters.				
				State Gross HP.				
				State Gross Torque.				
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	State Engine/Emissions Type.				
				State Urea Tank Size (in gallons), if required.				
		C.	Standard cooling system with antifreeze.					
		D.	Dry type air cleaner with service (restriction) indicator.					
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.					
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.					
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.					
TRANSMISSION:	20	A.	Automatic transmission, five (5)-speed minimum, with provisions for a PTO. Allison 2500RDS, or Approved Equivalent.					
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	State Manufacturer.	State Model No.			
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 9,000 lbs. capacity.					
		B.	Front shock absorbers.					
		C.	Front wheel oil-lubricated bearings and seals.					
		D.	Single speed rear axle and suspension, minimum 19,000 lbs. capacity. Rear axle ratio is to be a 5.57/5.71 for 2400 RPM engines, 5.57/5.71/5.86/5.88 for 2500 RPM engines, 6.14/6.43/6.50 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH.	State Rear Suspension Capacity (lbs.).	State Rear Axle Ratio.	State Engine RPM.	State Top Speed (MPH).	
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.					
		F.	Auxiliary rear leaf spring(s) or rubber helper.					
		G.	"No-Spin" or driver control traction differential (DCDL) on rear axle.					
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.					
		B.	Power steering.					

GROUP 3, NO. 25101601-330: 4 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 28,000 LBS. GVWR (4x2)								
GVWR* (lbs.) <sup>4</sup>	28,000		Payload Capacity (approx. lbs.) <sup>5</sup>	12,950				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE HAS FOUR (4) FULL SIZE DOORS AND IS RECOMMENDED TO TRANSPORT FOUR (4) TO SIX (6) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with two speakers and antenna.					
		B.	Air conditioner with integral heater and defroster.					
		C.	Arm rests both sides, if available; sun visors, both sides.					
		D.	Tinted glass all windows, including windshield.					
SAFETY ITEMS:	60	A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.					
		B.	Standard electric horn.					
		C.	Outside mirrors, left and right side. Mirrors to be six (6) x twelve (12) inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.					
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.					
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. <b>NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.</b>					
		F.	All access steps shall be self-cleaning slip-resistant grating.					
		G.	Daytime running lights.					
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.					
		B.	Spring applied parking brake.					
		C.	Front and rear automatic slack adjusters.					
		D.	Front and rear dust shields.					
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)					
		F.	Low air pressure warning indicator.					
		G.	<b>Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.</b>	<b>State Air Dryer with Heater Type.</b>				
TIRES & WHEELS:	70	A.	Six (6) 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.					
		B.	All wheels to be one-piece steel disc, ten (10)-hole, I.S.O. hub pilot mount, 22.5 inch diameter.					
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.					
CHASSIS, FRAME, CAB:	80	A.	<b>Minimum 28,000 lbs. GVWR, factory certified.</b>	<b>State GVWR lbs.</b>				
		B.	<b>Minimum 859,000 in-lbs. RBM frame.</b>	<b>State Frame RBM in lbs.</b>				
		C.	<b>Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of three (3) to five (5) inches.</b>	<b>State Cab/Body (CB) Clearance.</b>				
		D.	<b>Factory installed fuel tank(s), minimum 70 U.S. gallons.</b>	<b>State Fuel Tanks(s) Capacity.</b>				

GROUP 3, NO. 25101601-330: 4 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 28,000 LBS. GVWR (4x2)								
GVWR* (lbs.) <sup>4</sup>	28,000		Payload Capacity (approx. lbs.) <sup>5</sup>		12,950			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE HAS FOUR (4) FULL SIZE DOORS AND IS RECOMMENDED TO TRANSPORT FOUR (4) TO SIX (6) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
		E.	Front tow hooks or tow pins.					
		F.	Standard front bumper.					
CAB EQUIPMENT:	82	A.	Crew cab, 146.0 inch BBC, minimum, six (6) passenger, four (4) door model with tilt-type hood and fender assembly.	State BBC (Front bumper to back of cab) dimension.				
		B.	Bench front seat and full width rear bench seat or individual driver seat with two-man passenger seat and full width rear bench seat. Front and rear seats must match in color. Seats must have the same type fabric and pattern, if available.					
		C.	Grab handle(s) for cab entry, located at each entry door.					
		D.	Manufacturer's standard paint and colors.					
BODY:	84	A.	Four (4) cu. yd. dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-4 section 3.2.1.	State Body Manufacturer.				
				State Body Model No.				
				State Hoist Manufacturer.				
				State Hoist Model No.				
				State Tarp Manufacturer.				
				State Tarp Model No.				
		B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.					
		C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.					
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Customer/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.					
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.					
		C.	Paint numbers are referenced only to identify colors.					

GROUP 3, NO. 25101601-330: 4 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 28,000 LBS. GVWR (4x2)									
GVWR* (lbs.) <sup>4</sup>	28,000			Payload Capacity (approx. lbs.) <sup>5</sup>	12,950				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE HAS FOUR (4) FULL SIZE DOORS AND IS RECOMMENDED TO TRANSPORT FOUR (4) TO SIX (6) INDIVIDUALS.								
Bidder Name: <sup>7</sup>	<Insert Bidder Name>			Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
				0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>									
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>				
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>	
<b>OPTIONS:</b>	2004	A.	Manual transmission, six (6)-speed minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 9.01:1. Rear axle ratio shall be a 4.10/4.11 for 2400 RPM engines, 4.30/4.33 for 2500 RPM engines, 4.78/4.88 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant.	State Rear Axle Ratio.					(Credit)
				State Engine RPM.					
				State Top Speed (MPH).					
	3002	A.	Manufacturer's standard four-by-four (4x4) drive system model in lieu of base equipment four-by-two (4x2) model. Note: Provide only the difference in price between the two wheel drive model and the manufacturer's standard four-by-four (4x4) model offered.						(Credit)
	5001	A.	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.						
	6001	A.	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately thirty-six (36) inches in length located on the left and right front corners of the vehicle.)						
	6201	A.	Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable. See section 3.2.						
	7001	A.	Tubeless radial tires with on/off highway tread for rear only. Bid four (4) 11R22.5G (14PR) or larger tires for on/off highway use and two (2) 11R22.5G (14PR) or larger tires for highway use. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	State Front Tire Code.					
				State Rear Tire Code.					
	8001	A.	Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than fourteen (14) inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.						
	8002	A.	Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.						
	8201	A.	Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).						
	8202	A.	Two-tone colors. Manufacturer's standard two-tone colors.						
8401	A.	Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 2000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.							

GROUP 3, NO. 25101601-340: 5 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 33,000 LBS. GVWR (4x2)							
GVWR* (lbs.) <sup>4</sup>	33,000		Payload Capacity (approx. lbs.) <sup>5</sup>	17,350			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE HAS FOUR (4) FULL SIZE DOORS AND IS RECOMMENDED TO TRANSPORT FOUR (4) TO SIX (6) INDIVIDUALS.						
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>	
			0	0	\$ -	0.0%	
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>							
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>		
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>
ENGINE:	10	A.	Diesel engine, 5.9L, 210 Gross HP (per the latest issue of SAE J1349) and 560 lbs.-ft. Gross Torque, minimum.	State Liters.			
				State Gross HP.			
				State Gross Torque.			
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	State Engine/Emissions Type.			
				State Urea Tank Size (in gallons), if required.			
		C.	Standard cooling system with antifreeze.				
		D.	Dry type air cleaner with service (restriction) indicator.				
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.				
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.				
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.				
TRANSMISSION:	20	A.	Automatic transmission, six (6)-speed minimum, (International may bid a five (5)-speed, if required for the engine bid) with provisions for a PTO. Allison 3500RDS, or Approved Equivalent.				
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	State Manufacturer.			
				State Model No.			
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 12,000 lbs. capacity.				
		B.	Front shock absorbers.				
		C.	Front wheel oil-lubricated bearings and seals.				
		D.	Single speed rear axle and suspension, minimum 21,000 lbs. capacity. Rear axle ratio is to be a 6.14/6.43/6.50 for 2400 RPM engines, 6.50/6.83/6.86 for 2500 RPM engines, 6.43/6.50 for a 2800 RPM engine, (International - 6.14/6.17 for a 2600 RPM engine), or the closest possible ratio available that will provide a top speed of approximately 65 MPH.	State Rear Suspension Capacity (lbs.).			
				State Rear Axle Ratio.			
				State Engine RPM.			
				State Top Speed (MPH).			
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.				
		F.	Auxiliary rear leaf spring(s) or rubber helper.				
		G.	"No-Spin" or driver control traction differential (DCDL) on rear axle.				
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.				
		B.	Power steering.				

GROUP 3, NO. 25101601-340: 5 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 33,000 LBS. GVWR (4x2)								
GVWR* (lbs.) <sup>4</sup>	33,000		Payload Capacity (approx. lbs.) <sup>5</sup>		17,350			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE HAS FOUR (4) FULL SIZE DOORS AND IS RECOMMENDED TO TRANSPORT FOUR (4) TO SIX (6) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with two speakers and antenna.					
		B.	Air conditioner with integral heater and defroster.					
		C.	Arm rests both sides, if available; sun visors, both sides.					
		D.	Tinted glass all windows, including windshield.					
SAFETY ITEMS:	60	A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.					
		B.	Standard electric horn.					
		C.	Outside mirrors, left and right side. Mirrors to be six (6) x twelve (12) inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.					
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.					
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. <b>NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.</b>					
		F.	All access steps shall be self-cleaning slip-resistant grating.					
		G.	Daytime running lights.					
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.					
		B.	Spring applied parking brake.					
		C.	Front and rear automatic slack adjusters.					
		D.	Front and rear dust shields.					
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)					
		F.	Low air pressure warning indicator.					
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	State Air Dryer with Heater Type.				
TIRES & WHEELS:	70	A.	Six (6) 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.					
		B.	All wheels to be one-piece steel disc, ten (10)-hole, I.S.O. hub pilot mount, 22.5 inch diameter.					
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.					

GROUP 3, NO. 25101601-340: 5 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 33,000 LBS. GVWR (4x2)							
GVWR* (lbs.) <sup>4</sup>	33,000		Payload Capacity (approx. lbs.) <sup>5</sup>	17,350			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE HAS FOUR (4) FULL SIZE DOORS AND IS RECOMMENDED TO TRANSPORT FOUR (4) TO SIX (6) INDIVIDUALS.						
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>	
			0	0	\$ -	0.0%	
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>							
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>		
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>
CHASSIS, FRAME, CAB:	80	A.	Minimum 33,000 lbs. GVWR, factory certified.	State GVWR lbs.			
		B.	Minimum 1,700,000 in-lbs. RBM frame.	State Frame RBM in lbs.			
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of three (3) to five (5) inches.	State Cab/Body (CB) Clearance.			
		D.	Factory installed fuel tank(s), minimum 70 U.S. gallons.	State Fuel Tanks(s) Capacity.			
		E.	Front tow hooks or tow pins.				
		F.	Standard front bumper.				
CAB EQUIPMENT:	82	A.	Crew cab, 146.0 inch BBC, minimum, six (6) passenger, four (4) door model with tilt-type hood and fender assembly.	State BBC (Front bumper to back of cab) dimension.			
		B.	Bench front seat and full width rear bench seat or individual driver seat with two (2)-man passenger seat and full width rear bench seat. Front and rear seats must match in color. Seats must have the same type fabric and pattern, if available.				
		C.	Grab handle(s) for cab entry, located at each entry door.				
		D.	Manufacturer's standard paint and colors.				
BODY:	84	A.	Five (5) cu. yd. dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-5 section 3.2.1.	State Body Manufacturer.			
				State Body Model No.			
				State Hoist Manufacturer.			
	State Hoist Model No.						
	State Tarp Manufacturer.						
B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.						
C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.						
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Customer/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.				
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.				
		C.	Paint numbers are referenced only to identify colors.				



GROUP 3, NO. 25101601-340: 5 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 33,000 LBS. GVWR (4x2)								
GVWR* (lbs.) <sup>4</sup>	33,000		Payload Capacity (approx. lbs.) <sup>5</sup>	17,350				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE HAS FOUR (4) FULL SIZE DOORS AND IS RECOMMENDED TO TRANSPORT FOUR (4) TO SIX (6) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
<b>OPTIONS:</b>	2004	A.	Manual transmission, six (6)-speed minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 9.01:1. Rear axle ratio shall be a 4.10/4.11 for 2400 RPM engines, 4.30/4.33 for 2500 RPM engines, 4.88/4.89 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant.	State Rear Axle Ratio.				(Credit)
				State Engine RPM.				
				State Top Speed (MPH).				
	3002	A.	Manufacturer's standard four-by-four (4x4) drive system model in lieu of base equipment four-by-two (4x2) model. Note: Provide only the difference in price between the two wheel drive model and the manufacturer's standard four-by-four (4x4) model offered.					(Credit)
	5001	A.	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.					
	6001	A.	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately thirty-six (36) inches in length located on the left and right front corners of the vehicle.)					
	6201	A.	Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable. See section 3.2.					
	7001	A.	Tubeless radial tires with on/off highway tread for rear only. Bid four (4) 11R22.5G (14PR) or larger tires for on/off highway use and two (2) 11R22.5G (14PR) or larger tires for highway use. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	State Front Tire Code.				
				State Rear Tire Code.				
	8001	A.	Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than fourteen (14) inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.					
8002	A.	Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.						
8201	A.	Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).						
8202	A.	Two-tone colors. Manufacturer's standard two-tone colors.						
8401	A.	Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 2000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.						

GROUP 3, NO. 25101601-350: 8 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)							
GVWR* (lbs.) <sup>4</sup>	52,000		Payload Capacity (approx. lbs.) <sup>5</sup>	30,550			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC., AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.						
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>	
			0	0	\$ -	0.0%	
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>							
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>		
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>
ENGINE:	10	A.	Diesel engine, wet sleeve, 7.6L, 260 Gross HP (per the latest issue of SAE J1349) and 800 lbs.-ft. Gross Torque, minimum.	State Liters.			
				State Gross HP.			
				State Gross Torque.			
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	State Engine/Emissions Type.			
				State Urea Tank Size (in gallons), if required.			
		C.	Standard cooling system with antifreeze.				
		D.	Dry type air cleaner with service (restriction) indicator.				
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.				
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.				
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.				
TRANSMISSION:	20	A.	Automatic transmission, six (6)-speed minimum, with provisions for a PTO. Allison 3500RDS, or Approved Equivalent.				
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	State Manufacturer.			
				State Model No.			
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 12,000 lbs. capacity.				
		B.	Front shock absorbers.				
		C.	Front wheel oil-lubricated bearings and seals.				
		D.	Single speed tandem drive rear axle, minimum 40,000 lbs. capacity. Rear axle ratio is to be a 6.14/6.17 for 2200 RPM engines, 6.43/6.50 for 2400 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Minimum 40,000 lbs. rear suspension with minimum 52 inch steel walking beams. Hendrickson RT2-400/RT403, or Approved Equivalent.	State Rear Suspension Type.			
				State Rear Suspension Capacity (lbs.).			
				State Rear Axle Ratio.			
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.	State Engine RPM.			
		F.	"No-Spin" or driver control traction differential (DCDL) on the rearmost axle or both rear axles.	State Top Speed (MPH).			
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.				
		B.	Power steering.				

GROUP 3, NO. 25101601-350: 8 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)								
GVWR* (lbs.) <sup>4</sup>	52,000		Payload Capacity (approx. lbs.) <sup>5</sup>		30,550			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC., AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>		Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>	
			0		0	\$ -	0.0%	
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with two speakers and antenna.					
		B.	Air conditioner with integral heater and defroster.					
		C.	Arm rests both sides, if available; sun visors, both sides.					
		D.	Tinted glass all windows, including windshield.					
SAFETY ITEMS:	60	A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.					
		B.	Standard electric horn.					
		C.	Outside mirrors, left and right side. Mirrors to be six (6) x twelve (12) inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.					
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.					
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. <b>NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.</b>					
		F.	All access steps shall be self-cleaning slip-resistant grating.					
		G.	Daytime running lights.					
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.					
		B.	Spring applied parking brake.					
		C.	Front and rear automatic slack adjusters.					
		D.	Front and rear dust shields.					
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)					
		F.	Low air pressure warning indicator.					
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	State Air Dryer with Heater Type.				
TIRES & WHEELS:	70	A.	Ten (10) 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.					
		B.	All wheels to be one-piece steel disc, ten (10)-hole, I.S.O. hub pilot mount, 22.5 inch diameter.					
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.					
CHASSIS, FRAME, CAB:	80	A.	Minimum 52,000 lbs. GVWR, factory certified.	State GVWR lbs.				
		B.	Minimum 2,400,000 in-lbs. RBM frame.	State Frame RBM in lbs.				
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of three (3) to five (5) inches.	State Cab/Body (CB) Clearance.				
		D.	Factory installed fuel tank(s), minimum 100 U.S. gallons. State fuel tank(s) capacity.	State Fuel Tanks(s) Capacity.				

GROUP 3, NO. 25101601-350: 8 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)												
GVWR* (lbs.) <sup>4</sup>	52,000		Payload Capacity (approx. lbs.) <sup>5</sup>		30,550							
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC., AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.											
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>		Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>					
			0		0	\$ -	0.0%					
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>												
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>							
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>				
CAB EQUIPMENT:	82	E.	Front tow hooks or tow pins.									
		F.	Standard front bumper.									
		A.	Conventional cab, with tilt-type hood and fender assembly.									
		B.	High back air suspension driver seat with matching fixed base companion seat.									
		C.	Grab handle(s) for cab entry, located at each entry door.									
D.	Manufacturer's standard paint and colors.											
E.	Rear cab window with fixed tinted glass.											
BODY:	84	A.	Eight (8) cubic yard heavy-duty dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-8 section 3.2.1.	State Body Manufacturer.								
		State Body Model No.										
		State Hoist Manufacturer.										
State Hoist Model No.												
State Tarp Manufacturer.												
State Tarp Model No.												
B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.											
C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.											
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/ Customer/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.									
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.									
		C.	Paint numbers are referenced only to identify colors.									

GROUP 3, NO. 25101601-350: 8 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)									
GVWR* (lbs.) <sup>4</sup>	52,000			Payload Capacity (approx. lbs.) <sup>5</sup>	30,550				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC., AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.								
Bidder Name: <sup>7</sup>	<Insert Bidder Name>			Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
				0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>									
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>				
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>	
OPTIONS:	2010	A.	Direct drive manual transmission, ten (10) forward speeds minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 19.00:1. Rear axle ratio shall be a 3.90 for 2200 RPM engines, 4.11 for 2400 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant. Minimum fourteen (14) inch diameter, two (2)-plate ceramic-faced clutch. NOTE: Include the credit for a manual transmission PTO as specified in the enclosed dump body specification.	State Rear Axle Ratio.				(Credit)	
				State Engine RPM.					
				State Top Speed (MPH).					
		5001	A.	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.					
		6001	A.	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately thirty-six (36) inches in length located on the left and right front corners of the vehicle.)					
		6201	A.	Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable. See section 3.2.					
		7001	A.	Tubeless radial tires with on/off highway tread for rear only. Bid eight (8) 11R22.5G (14PR) or larger tires for on/off highway use and two (2) 11R22.5G (14PR) or larger tires for on highway use. Bid in lieu of base tires. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	State Front Tire Code.				
					State Rear Tire Code.				
		8001	A.	Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than fourteen (14) inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.					
		8002	A.	Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.					
		8201	A.	Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).					
		8202	A.	Two-tone colors. Manufacturer's standard two-tone colors.					
		8204	A.	High back air suspension passenger seat. Bid in lieu of the matching fixed base passenger seat specified in Section 82.B.					
	8402	A.	Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 3000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.						

GROUP 3, NO. 25101601-360: 8 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)						
GVWR* (lbs.) <sup>4</sup>	52,000		Payload Capacity (approx. lbs.) <sup>5</sup>	30,550		
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.					
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>
			0	0	\$ -	0.0%
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>						
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>	
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>
ENGINE:	10	A.	Diesel engine, 7.2L, 260 Gross HP (per the latest issue of SAE J1349) and 800 lbs.-ft. Gross Torque, minimum.	State Liters.		
				State Gross HP.		
				State Gross Torque.		
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	State Engine/Emissions Type.		
				State Urea Tank Size (in gallons), if required.		
		C.	Standard cooling system with antifreeze.			
		D.	Dry type air cleaner with service (restriction) indicator.			
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.			
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.			
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.			
TRANSMISSION:	20	A.	Automatic transmission, six (6)-speed minimum, with provisions for a PTO. Allison 3500RDS, or Approved Equivalent.			
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	State Manufacturer.		
				State Model No.		
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 12,000 lbs. capacity.			
		B.	Front shock absorbers.			
		C.	Front wheel oil-lubricated bearings and seals.			
		D.	Single speed tandem drive rear axle, minimum 40,000 lbs. capacity. Rear axle ratio is to be a 6.14/6.17 for 2200 RPM engines, 6.43/6.50 for 2400, 6.83 for 2500 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Minimum 40,000 lbs. rear suspension with minimum 52 inch steel walking beams. Hendrickson RT2-400/RT403, or Approved Equivalent.	State Rear Suspension Type.		
				State Rear Suspension Capacity (lbs.).		
				State Rear Axle Ratio.		
				State Engine RPM.		
				State Top Speed (MPH).		
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.			
		F.	"No-Spin" or driver control traction differential (DCDL) on the rearmost axle or both axles.			
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.			
		B.	Power steering.			
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with two speakers and antenna.			
		B.	Air conditioner with integral heater and defroster.			
		C.	Arm rests both sides, if available; sun visors, both sides.			
		D.	Tinted glass all windows, including windshield.			

GROUP 3, NO. 25101601-360: 8 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)							
GVWR* (lbs.) <sup>4</sup>	52,000		Payload Capacity (approx. lbs.) <sup>5</sup>		30,550		
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.						
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>		Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>
			0		0	\$ -	0.0%
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>							
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>		
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>
SAFETY ITEMS:	60	A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.				
		B.	Standard electric horn.				
		C.	Outside mirrors, left and right side. Mirrors to be six (6) x twelve (12) inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.				
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.				
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. <b>NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.</b>				
		F.	All access steps shall be self-cleaning slip-resistant grating.				
		G.	Daytime running lights.				
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.				
		B.	Spring applied parking brake.				
		C.	Front and rear automatic slack adjusters.				
		D.	Front and rear dust shields.				
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)				
		F.	Low air pressure warning indicator.				
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	State Air Dryer with Heater Type.			
TIRES & WHEELS:	70	A.	Ten (10) 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.				
		B.	All wheels to be one-piece steel disc, ten (10)-hole, I.S.O. hub pilot mount, 22.5 inch diameter.				
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.				
CHASSIS, FRAME, CAB:	80	A.	Minimum 52,000 lbs. GVWR, factory certified.	State GVWR lbs.			
		B.	Minimum 2,400,000 in-lbs. RBM to rear end of frame, factory reinforced if necessary.	State Frame RBM in lbs.			
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of three (3) to five (5) inches.	State Cab/Body (CB) Clearance.			
		D.	Factory installed fuel tank(s), minimum 100 U.S. gallons. State fuel tank(s) capacity.	State Fuel Tanks(s) Capacity.			
		E.	Front tow hooks or tow pins.				
		F.	Standard front bumper.				

GROUP 3, NO. 25101601-360: 8 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)								
GVWR* (lbs.) <sup>4</sup>	52,000		Payload Capacity (approx. lbs.) <sup>5</sup>		30,550			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>		Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>	
			0		0	\$ -	0.0%	
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.					
		B.	High back air suspension driver seat with matching fixed base companion seat.					
		C.	Grab handle(s) for cab entry, located at each entry door.					
		D.	Manufacturer's standard paint and colors.					
		E.	Rear cab window with fixed tinted glass.					
BODY:	84	A.	Eight (8) cubic yard heavy-duty dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-8 section 3.2.1.	State Body Manufacturer.				
		State Body Model No.						
		State Hoist Manufacturer.						
		State Hoist Model No.						
B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.		State Tarp Manufacturer.					
C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.		State Tarp Model No.					
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Customer/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.					
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.					
		C.	Paint numbers are referenced only to identify colors.					



**GROUP 3, NO. 25101601-360: 8 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)**

<b>GVWR* (lbs.)<sup>4</sup></b>	<b>52,000</b>	<b>Payload Capacity (approx. lbs.)<sup>5</sup></b>	<b>30,550</b>
<b>Intended Use:</b>	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.		
<b>Bidder Name:<sup>7</sup></b>	<Insert Bidder Name>	<b>Representative Model:<sup>9</sup></b>	<b>Rep. Model Number:<sup>10</sup></b>
		<b>0</b>	<b>0</b>
		<b>BV Price:<sup>11</sup></b>	<b>OEM Options Discount:<sup>13</sup></b>
		\$ -	<b>0.0%</b>

**Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.**

Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>					
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>		
<b>OPTIONS:</b>	2010	A.	Direct drive manual transmission, ten (10) forward speeds minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 19.00:1. Rear axle ratio shall be a 3.90 for 2200 RPM engines, 4.11 for 2400 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant. Minimum fourteen (14) inch diameter, two (2)-plate ceramic-faced clutch. NOTE: Include the credit for a manual transmission PTO as specified in the enclosed dump body specification.	State Rear Axle Ratio.					<b>(Credit)</b>	
				State Engine RPM.						
				State Top Speed (MPH).						
		5001	A.	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.						
		6001	A.	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately thirty-six (36) inches in length located on the left and right front corners of the vehicle.)						
		6201	A.	Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable. See section 3.2.						
		7001	A.	Tubeless radial tires with on/off highway tread for rear only. Bid eight (8) 11R22.5G (14PR) or larger tires for on/off highway use and two (2) 11R22.5G (14PR) or larger tires for on highway use. Bid in lieu of base tires. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	State Front Tire Code.					
					State Rear Tire Code.					
		8001	A.	Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than fourteen (14) inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.						
					<b>PURCHASER MUST SPECIFY BODY LENGTH AND TYPE (DUMP, STAKE, ETC.) IN ORDER FOR THE DEALER TO INSTALL THE PINTLE HOOK IN THE PROPER LOCATION</b>					
		8002	A.	Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.						
		8201	A.	Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).						
		8202	A.	Two-tone colors. Manufacturer's standard two-tone colors.						
	8204	A.	High back air suspension passenger seat. Bid in lieu of the matching fixed base passenger seat specified in Section 82.B.							
	8402	A.	Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 3000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.							

GROUP 3, NO. 25101601-370: 12 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)								
GVWR* (lbs.) <sup>4</sup>	64,000		Payload Capacity (approx. lbs.) <sup>5</sup>	41,800				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
ENGINE:	10	A.	Diesel engine, wet sleeve, 8.8L, 330 Gross HP (per the latest issue of SAE J1349) and 1100 lbs.-ft. Gross Torque, minimum.	State Liters.				
				State Gross HP.				
				State Gross Torque.				
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	State Engine/Emissions Type.				
				State Urea Tank Size (in gallons), if required.				
		C.	Standard cooling system with antifreeze.					
		D.	Dry type air cleaner with service (restriction) indicator.					
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.					
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.					
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.					
TRANSMISSION:	20	A.	Manual overdrive transmission, ten (10) forward speeds minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 14.56:1.					
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	State Manufacturer.				
				State Model No.				
		C.	Transmission shall be filled with synthetic lubricant.					
		D.	Minimum fourteen (14) inch diameter two (2)-plate ceramic-faced clutch.					
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 18,000 lbs. capacity.					
		B.	Front shock absorbers.					
		C.	Front wheel oil-lubricated bearings and seals.					
		D.	Single speed tandem drive rear axle, minimum 46,000 lbs. capacity. Rear axle ratio is to be a 4.88/4.89, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Minimum 46,000 lbs. rear suspension with minimum 54 inch steel walking beams. Hendrickson RT2-460/RT463, Mack Camelback, or Approved Equivalent.	State Rear Suspension Type.				
				State Rear Suspension Capacity (lbs.).				
				State Rear Axle Ratio.				
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.					
		F.	"No-Spin" or driver control traction differential (DCDL) on the rearmost axle or both axles.					
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.					
		B.	Power steering.					

GROUP 3, NO. 25101601-370: 12 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)								
GVWR* (lbs.) <sup>4</sup>	64,000		Payload Capacity (approx. lbs.) <sup>5</sup>	41,800				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with two speakers and antenna.					
		B.	Air conditioner with integral heater and defroster.					
		C.	Arm rests both sides, if available; sun visors, both sides.					
		D.	Tinted glass all windows, including windshield.					
SAFETY ITEMS:	60	A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.					
		B.	Standard electric horn.					
		C.	Outside mirrors, left and right side. Mirrors to be six (6) x twelve (12) inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.					
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.					
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. <b>NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.</b>					
		F.	All access steps shall be self-cleaning slip-resistant grating.					
		G.	Daytime running lights.					
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.					
		B.	Spring applied parking brake.					
		C.	Front and rear automatic slack adjusters.					
		D.	Front and rear dust shields.					
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)					
		F.	Low air pressure warning indicator.					
		G.	<b>Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.</b>	<b>State Air Dryer with Heater Type.</b>				
TIRES & WHEELS:	70	A.	Tubeless radial tires with highway tread. Bid eight (8) 11R22.5H (16 PR) or larger rear tires and two (2) 385/65R22.5J (18PR) or larger front tires.					
		B.	All wheels to be one-piece steel disc, ten (10)-hole, I.S.O. hub pilot mount, 22.5 inch diameter.					
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.					

GROUP 3, NO. 25101601-370: 12 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)								
GVWR* (lbs.) <sup>4</sup>	64,000		Payload Capacity (approx. lbs.) <sup>5</sup>	41,800				
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>		
			0	0	\$ -	0.0%		
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
CHASSIS, FRAME, CAB:	80	A.	Minimum 64,000 lbs. GVWR, factory certified.	State GVWR lbs.				
		B.	Minimum 2,700,000 in-lbs. RBM to rear end of frame, factory reinforced if necessary.	State Frame RBM in lbs.				
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of three (3) to five (5) inches.	State Cab/Body (CB) Clearance.				
		D.	Factory installed fuel tank(s), minimum 100 U.S. gallons. State fuel tank(s) capacity.	State Fuel Tanks(s) Capacity.				
		E.	Front tow hooks or tow pins.					
		F.	Standard front bumper.					
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.					
		B.	High back air suspension driver seat with matching fixed base companion seat.					
		C.	Grab handle(s) for cab entry, located at each entry door.					
		D.	Manufacturer's standard paint and colors.					
		E.	Rear cab window with fixed tinted glass.					
BODY:	84	A.	Twelve (12) cubic yard heavy-duty dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-12 section 3.2.1.	State Body Manufacturer.				
		State Body Model No.						
		State Hoist Manufacturer.						
State Hoist Model No.								
State Tarp Manufacturer.								
State Tarp Model No.								
B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.							
C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.							
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Customer/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.					
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.					
		C.	Paint numbers are referenced only to identify colors.					

GROUP 3, NO. 25101601-370: 12 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)							
GVWR* (lbs.) <sup>4</sup>	64,000		Payload Capacity (approx. lbs.) <sup>5</sup>	41,800			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.						
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>	
			0	0	\$ -	0.0%	
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>							
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>		
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>
<b>OPTIONS:</b>	5001	A.	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.				
	6001	A.	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately thirty-six (36) inches in length located on the left and right front corners of the vehicle.)				
	6201	A.	Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable. See section 3.2.				
	7001	A.	Tubeless radial tires with on/off highway tread for rear only. Bid eight (8) 11R22.5H (16PR) or larger tires for on/off highway use. Bid in lieu of base tires. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	State Front Tire Code.			
				State Rear Tire Code.			
	8001	A.	Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than fourteen (14) inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.				
			<b>PURCHASER MUST SPECIFY BODY LENGTH AND TYPE (DUMP, STAKE, ETC.) IN ORDER FOR THE DEALER TO INSTALL THE PINTLE HOOK IN THE PROPER LOCATION</b>				
	8002	A.	Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.				
	8201	A.	Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).				
	8202	A.	Two-tone colors. Manufacturer's standard two-tone colors.				
	8204	A.	High back air suspension passenger seat. Bid in lieu of the matching fixed base passenger seat specified in Section 82.B.				
8401	A.	Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 3000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.					
8410	A.	Twin telescopic hoist for twelve (12) cubic yard dump body. Galion UT66392, Heil Model HP2T52-72, Warren CFT-5397, or Approved Equivalent. Hoist is to be an N.T.E.A. Class 110, minimum. Bid in lieu of hoist specified in DUMP-12.					

GROUP 3, NO. 25101601-380: 12 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)						
GVWR* (lbs.) <sup>4</sup>	64,000		Payload Capacity (approx. lbs.) <sup>5</sup>	41,800		
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.					
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>
			0	0	\$ -	0.0%
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>						
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>	
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>
ENGINE:	10	A.	Diesel engine, wet sleeve, 8.3L, 285 Gross HP (per the latest issue of SAE J1349) and 800 lbs.-ft. Gross Torque, minimum.	State Liters.		
				State Gross HP.		
				State Gross Torque.		
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	State Engine/Emissions Type.		
				State Urea Tank Size (in gallons), if required.		
		C.	Standard cooling system with antifreeze.			
		D.	Dry type air cleaner with service (restriction) indicator.			
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.			
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.			
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.			
TRANSMISSION:	20	A.	Automatic transmission, six (6)-speed minimum, with provisions for a PTO. Allison 3500RDS, or Approved Equivalent.			
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	State Manufacturer.		
				State Model No.		
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 18,000 lbs. capacity.			
		B.	Front shock absorbers.			
		C.	Front wheel oil-lubricated bearings and seals.			
		D.	Single speed tandem drive rear axle, minimum 46,000 lbs. capacity. Rear axle ratio is to be a 6.14/6.17, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Minimum 46,000 lbs. rear suspension with minimum 54 inch steel walking beams. Hendrickson RT2-460/RT463, or Approved Equivalent.	State Rear Suspension Type.		
				State Rear Suspension Capacity (lbs.).		
				State Rear Axle Ratio.		
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.	State Top Speed (MPH).		
		F.	"No-Spin" or driver control traction differential (DCDL) on the rearmost axle or both rear axles.			
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.			
		B.	Power steering.			
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with two speakers and antenna.			
		B.	Air conditioner with integral heater and defroster.			
		C.	Arm rests both sides, if available; sun visors, both sides.			
		D.	Tinted glass all windows, including windshield.			

GROUP 3, NO. 25101601-380: 12 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)							
GVWR* (lbs.) <sup>4</sup>	64,000		Payload Capacity (approx. lbs.) <sup>5</sup>		41,800		
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.						
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>		Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>
			0		0	\$ -	0.0%
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>							
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>		
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>
SAFETY ITEMS:	60	A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.				
		B.	Standard electric horn.				
		C.	Outside mirrors, left and right side. Mirrors to be six (6) x twelve (12) inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.				
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.				
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. <b>NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.</b>				
		F.	All access steps shall be self-cleaning slip-resistant grating.				
		G.	Daytime running lights.				
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.				
		B.	Spring applied parking brake.				
		C.	Front and rear automatic slack adjusters.				
		D.	Front and rear dust shields.				
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)				
		F.	Low air pressure warning indicator.				
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	State Air Dryer with Heater Type.			
TIRES & WHEELS:	70	A.	Tubeless radial tires with highway tread. Bid eight (8) 11R22.5H (16 PR) or larger rear tires and two (2) 385/65R22.5J (18PR) or larger front tires.				
		B.	All wheels to be one-piece steel disc, ten (10)-hole, I.S.O. hub pilot mount, 22.5 inch diameter.				
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.				
CHASSIS, FRAME, CAB:	80	A.	Minimum 64,000 lbs. GVWR, factory certified.	State GVWR lbs.			
		B.	Minimum 2,700,000 in-lbs. RBM to rear end of frame, factory reinforced if necessary.	State Frame RBM in lbs.			
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of three (3) to five (5) inches.	State Cab/Body (CB) Clearance.			
		D.	Factory installed fuel tank(s), minimum 100 U.S. gallons. State fuel tank(s) capacity.	State Fuel Tanks(s) Capacity.			
		E.	Front tow hooks or tow pins.				
		F.	Standard front bumper.				

GROUP 3, NO. 25101601-380: 12 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)								
GVWR* (lbs.) <sup>4</sup>	64,000		Payload Capacity (approx. lbs.) <sup>5</sup>		41,800			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.							
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>		Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>	
			0		0	\$ -	0.0%	
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>								
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>			
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>	PRICE: <sup>26</sup>
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.					
		B.	High back air suspension driver seat with matching fixed base companion seat.					
		C.	Grab handle(s) for cab entry, located at each entry door.					
		D.	Manufacturer's standard paint and colors.					
		E.	Rear cab window with fixed tinted glass.					
BODY:	84	A.	Twelve (12) cubic yard heavy-duty dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification DUMP-12 section 3.2.1.	State Body Manufacturer.				
				State Body Model No.				
				State Hoist Manufacturer.				
				State Hoist Model No.				
				State Tarp Manufacturer.				
				State Tarp Model No.				
		B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.					
		C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.					
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Customer/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.					
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.					
		C.	Paint numbers are referenced only to identify colors.					
OPTIONS:	5001	A.	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.					
	6001	A.	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately thirty-six (36) inches in length located on the left and right front corners of the vehicle.)					
	6201	A.	Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable. See section 3.2.					



GROUP 3, NO. 25101601-380: 12 YARD DUMP TRUCK, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)							
GVWR* (lbs.) <sup>4</sup>	64,000		Payload Capacity (approx. lbs.) <sup>5</sup>	41,800			
Intended Use:	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC. AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.						
Bidder Name: <sup>7</sup>	<Insert Bidder Name>		Representative Model: <sup>9</sup>	Rep. Model Number: <sup>10</sup>	BV Price: <sup>11</sup>	OEM Options Discount: <sup>13</sup>	
			0	0	\$ -	0.0%	
<b>Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.</b>							
Specification Category: <sup>16</sup>	Section: <sup>17</sup>	Sub-Section: <sup>18</sup>	Base Vehicle Specification: <sup>19</sup>	Representative Model Specification: <sup>20</sup>	Options Specification Information: <sup>21</sup>		
					MFR.: <sup>22</sup>	MODEL NO.: <sup>23</sup>	CODE/ CA Code: <sup>25</sup>
	7001	A.	Tubeless radial tires with on/off highway tread for rear only. Bid eight (8) 11R22.5H (16PR) or larger tires for on/off highway use. Bid in lieu of base tires. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	State Front Tire Code.			
				State Rear Tire Code.			
	8001	A.	Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than fourteen (14) inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.				
				<b>PURCHASER MUST SPECIFY BODY LENGTH AND TYPE (DUMP, STAKE, ETC.) IN ORDER FOR THE DEALER TO INSTALL THE PINTLE HOOK IN THE PROPER LOCATION.</b>			
	8002	A.	Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.				
	8201	A.	Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).				
	8202	A.	Two-tone colors. Manufacturer's standard two-tone colors.				
	8204	A.	High back air suspension passenger seat. Bid in lieu of the matching fixed base passenger seat specified in Section 82.B.				
	8402	A.	Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 3000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.				
	8410	A.	Twin telescopic hoist for twelve (12) cubic yard dump body. Galion UT66392, HeilModel HP2T52-72, Warren CFT-5397, or Approved Equivalent. Hoist is to be an N.T.E.A. Class 110, minimum. Bid in lieu of hoist specified in DUMP-12.				