

ADDENDUM #001

Solicitation Number: FDC ITB-20-049
Solicitation Title: Windows for Jefferson Correctional Institution
Opening Date/Time: May 1, 2020 at 2:00 p.m. (Eastern Time)
Addendum Number: 001
Addendum Date: April 13, 2020

Failure to file a protest within the time prescribed in Section 120.57(3), Florida Statutes, or failure to post the bond or other security required by law within the time allowed for filing a bond shall constitute a waiver of proceedings under Chapter 120, Florida Statutes.

Please be advised that the information contained on the next page is applicable to the original specifications of the above referenced solicitation. Added language to the ITB is highlighted in yellow, while deleted language has been stricken.

This Addendum includes the following changes:

Change No. 1:

Section 2.1.1 Aluminum Windows, is hereby revised as follows:

2.1.1 Aluminum Windows

The Bidder shall provide aluminum windows, **from a single manufacturer**, that are fixed frame “uppers” with horizontal sliding lower. Frames and sashes shall have aluminum extrusions complying with the AAMA/WDMA/CSA 101/I.S.2/A440 standard.

All windows must have fabricated frames, sashes, and muntins with an integral, concealed, low-conductance thermal barrier located between exterior materials, and window members exposed on interior side in a manner that eliminates direct metal-to-metal contact. **The window frame shall have a depth of 3 3/8” made up of 6063 – T5 aluminum alloy with minimum wall thickness of 0.062.** The sliding unit shall be held within the window frame by Torx and Peg head fasteners that can be removed to allow removal of the frame for cleaning.

Window glazing shall be clear 1/4-inch, mar-resistant polycarbonate held in with extruded aluminum glazing bead. Approved brands include Makrolon and Lexan. Equivalent brands will require approval by the Department by providing specification documents by the last day for written inquiries noted in the Timeline. The Department will provide a response by the date for Written Responses to Written Inquiries noted in the Timeline.

The Bidder shall provide the manufacturer’s standard hardware fabricated from aluminum, stainless steel, carbon steel complying with the AAMA 907 standard, or other corrosion-resistant material compatible with adjacent materials designed to smoothly operate, tightly close, securely lock windows, and sized to accommodate sash weight and dimensions. Exposed hardware color and finish shall be the manufacturer’s standard.

Window hardware shall include the manufacturer's standard of dimensions and profile indicated for sill cap and track, designed to comply with performance requirements indicated, and to drain to the exterior.

Locks and latches shall allow unobstructed movement of the sash across adjacent sashes in the direction indicated and operate from the inside only. Roller assemblies shall have low-friction design.

The Bidder shall provide full-perimeter weather stripping for each operable sash unless otherwise indicated.

Window fasteners used in the manufacturing process shall be stainless steel, noncorrosive, and match the finish of the hardware. Screws and fasteners shall be Torx and Peg head compatible with window members, trim, hardware, anchors, and other components. Screws and fasteners shall be exposed to the least extent possible.

The Bidder shall also provide the following accessories:

- 1) Subsills: Extruded aluminum;
- 2) Interior Trim: Extruded aluminum; and
- 3) Panning Trim: Extruded aluminum.

REMAINDER OF PAGE INTENTIONALLY LEFT BLANK