

Attachment D.6 Price Sheet: Truck Tractor

Please see Attachment D: Instruction and General Information for Instructions, Color Key, and Reference Key.

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Please fill in the cells in yellow and soft yellow located in the columns below for the Representative Models your company bids on.

Attachment D.6 Price Sheet: Truck Tractor					Please fill in the cells in yellow and soft yellow located in the columns below for the Representative Models your company bids on.							
Please see Attachment D: Instruction and General Information for Instructions, Color Key, and Reference Key.					Bidder Name: ⁷		<Insert Bidder Name>					
Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.												
Group ¹	Contract Code ²	Base Vehicle Description ³	GVWR ⁴ (lbs.) ⁴	Accepted Brands ⁵	Manufacturer/Brand ⁸	Representative Model ⁹	Representative Model Number ¹⁰	Base Vehicle Price (\$###,###.00) ¹¹	OEM Options Discount (##%) ¹²	Calculated Score ¹³	Customer Pick Up Discount (\$###,###.00) ¹⁴	Estimated Lead-time in Days (###) ¹⁵
TRUCK TRACTOR	600	TRUCK TRACTOR, SINGLE AXLE, CLASS 8, 50,000 LBS. GCWR (4X2)	50,000	FREIGHTLINER M2, INTERNATIONAL 4000-SERIES, OR APPROVED EQUIVALENT						\$ -		
	610	TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 80,000 LBS. GCWR (6X4)	52,000	FREIGHTLINER M2, INTERNATIONAL 7000-SERIES, OR APPROVED EQUIVALENT						\$ -		
	620	TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 120,000 LBS. GCWR (6X4)	120,000	FREIGHTLINER 120-SERIES, INTERNATIONAL 5000-SERIES, OR APPROVED EQUIVALENT						\$ -		

GROUP 6, NO. 25102100-600: TRUCK TRACTOR, SINGLE AXLE, CLASS 8, 50,000 LBS. GCWR (4X2)

GVWR* (lbs.)⁴	50,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO INDIVIDUALS ON PAVED AND UNPAVED, GRADED ROADS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
ENGINE:	10	A.	Diesel engine, 7.2L, 260 Gross HP (per the latest issue of SAE J1349) and 800 lbs.-ft. Gross Torque, 2000 governed RPM, minimum.	State Liters.				
				State Gross HP.				
				State Gross Torque.				
				State Governed RPM.				
				State Engine/Emissions Type.				
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	State Urea Tank Size (in gallons), if required.				
		C.	Standard cooling system with antifreeze.					
D.	Dry type air cleaner with service (restriction) indicator.							
E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.							
F.	Vertical exhaust system or horizontal muffler with vertical exhaust pipe. Exhaust pipe must have a curved end or straight end protected with a rain cap.							
G.	Speed/cruise control.							
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.					
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.					
TRANSMISSION:	20	A.	Automatic transmission, six (6)-speed minimum, with provisions for a PTO. Allison 3000RDS or approved equivalent.					
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 12,000 lbs. capacity.					
		B.	Front shock absorbers.					
		C.	Front wheel oil-lubricated bearings and seals.					
		D.	Single speed rear axle and suspension, minimum 23,000 lbs. capacity. Rear axle ratio is to be a 6.14/6.17 for 2200 RPM engines, 6.43/6.50 for 2400, 6.83 for 2500 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH.	State Rear Suspension Capacity (lbs.).				
				State Rear Suspension Type.				
				State Rear Axle Ratio.				
E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.							
F.	Auxiliary rear springs, if available.							
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.					
		B.	Power steering.					

GROUP 6, NO. 25102100-600: TRUCK TRACTOR, SINGLE AXLE, CLASS 8, 50,000 LBS. GCWR (4X2)

GVWR* (lbs.)⁴	50,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO INDIVIDUALS ON PAVED AND UNPAVED, GRADED ROADS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category:¹⁶	Section:¹⁷	Sub-Section:¹⁸	Base Vehicle Specification:¹⁹	Representative Model Specification:²⁰	Options Specification Information:²¹			
					MFR.:²²	MODEL NO.:²³	CODE/ CA Code:²⁵	PRICE:²⁶
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with two speakers and antenna.					
		B.	Air conditioner with integral heater and defroster.					
		C.	Arm rests both sides, if available; sun visors, both sides.					
		D.	Tinted glass all windows, including windshield.					
SAFETY ITEMS:	60	A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.					
		B.	Standard electric horn.					
		C.	Outside mirrors, left and right side. Mirrors to be six (6) x twelve (12) inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.					
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.					
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.					
		F.	All access steps shall be self-cleaning slip-resistant grating.					
		G.	Daytime running lights.					
		H.	Rear quarter fenders, plastic, rubber or stainless steel. Factory or dealer installed. NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON FENDERS.					
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.					
		B.	Spring applied parking brake.					
		C.	Front and rear automatic slack adjusters.					
		D.	Front and rear dust shields.					
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)					
		F.	Low air pressure warning indicator.					
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	State Air Dryer with Heater Type.				
TIRES & WHEELS:	70	A.	Six (6) 11R22.5H (16PR) or larger, tubeless, radial tires with highway tread.					
		B.	All wheels to be one-piece steel disc, ten (10)-hole, I.S.O. hub pilot mount, 22.5 inch diameter.					
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.					

GROUP 6, NO. 25102100-600: TRUCK TRACTOR, SINGLE AXLE, CLASS 8, 50,000 LBS. GCWR (4X2)

GVWR* (lbs.)⁴	50,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO INDIVIDUALS ON PAVED AND UNPAVED, GRADED ROADS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹				
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶	
CHASSIS, FRAME, CAB:	80	A.	Minimum 35,000 lbs. GVWR, 50,000 lbs. GCWR, factory certified.	State GVWR lbs.					
		B.	Minimum 1,373,000 in-lbs. RBM to rear end of frame, factory reinforced if necessary.	State Frame RBM in lbs.					
		A.	Cab-to-axle dimension of 84-86 inches. NOTE TO RESPONDENT: IF MORE CAB-TO-AXLE DIMENSION IS REQUIRED TO PROVIDE THE CORRECT TRAILER SWING CLEARANCE, RESPONDENT MUST NOT PROVIDE ANY MORE THAN REQUIRED.	State Cab/Axle dimension.					
		NOTE: PURCHASER MUST PROVIDE THE CONTRACTOR WITH THE OVERALL WIDTH OF THE FRONT OF THE TRAILER AND THE KINGPIN LOCATION - DISTANCE FROM THE FRONT OF THE TRAILER TO THE KINGPIN.							
		D.	Factory installed fuel tank(s), minimum 100 U.S. gallons.	State Fuel Tanks(s) Capacity.					
		E.	Front tow hooks or tow pins.						
		F.	Standard front bumper.						
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.	State BBC (Front bumper to back of cab) dimension.					
		B.	High back air suspension driver seat with matching fixed base companion seat.						
		C.	Grab handle(s) for cab entry, located at each entry door.						
		D.	Manufacturer's standard paint and colors.						
		E.	Rear cab window with fixed tinted glass.						
TRACTOR ITEMS:	84	A.	Stationary fifth wheel. Simplex II, Holland FW 35-Series, Fontaine SL6FMA, SL6PMA or approved equivalent. Factory or dealer installed. Fifth wheel height (unloaded) must range from 48 inches minimum to 50 inches maximum. Specified height is the distance from the ground to the top of the fifth wheel.	State Manufacturer.					
				State Model No.					
				State Fifth Wheel Height (unloaded).					
				State Slide Travel Length.					
		B.	Hand controlled trailer brake connection and double check breakaway valves.						
		C.	Minimum twelve (12) foot coiled tractor/trailer brake hoses with hanger.						
		D.	Minimum twelve (12) foot coiled tractor/trailer seven wire light cable with adapter plug.						
		E.	Heavy-duty aluminum fifth wheel safety platform, minimum twenty-four (24) inches in length. Factory or dealer installed.						

GROUP 6, NO. 25102100-600: TRUCK TRACTOR, SINGLE AXLE, CLASS 8, 50,000 LBS. GCWR (4X2)

GVWR* (lbs.)⁴	50,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO INDIVIDUALS ON PAVED AND UNPAVED, GRADED ROADS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category:¹⁶	Section:¹⁷	Sub-Section:¹⁸	Base Vehicle Specification:¹⁹	Representative Model Specification:²⁰	Options Specification Information:²¹			
					MFR.:²²	MODEL NO.:²³	CODE/ CA Code:²⁵	PRICE:²⁶
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/ Customer/ Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.					
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.					
		C.	Paint numbers are referenced only to identify colors.					
OPTIONS:	2002	A.	"Hot Shift" power take-off (PTO) with a SAE standard, keyed output shaft, installed. To include a dash mounted electric-over-hydraulic switch and indicator light. Chelsea 276, Muncie CS Series, or Approved Equivalent. For automatic transmission only.					
	2003	A.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.					
	3001	A.	"No-Spin" or driver control traction differential (DCDL) on rear axle.					
	5001	A.	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.					
	6001	A.	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately thirty-six (36) inches in length located on the left and right front corners of the vehicle.)					
	6201	A.	Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable. See section 3.2.					
	7001	A.	Tubeless radial tires with on/off highway tread for rear only. Bid four (4) 11R22.5H (16PR) or larger tires for on/off highway use. Rear tires to be General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Con RR150, Continental HDL, or approved equivalent.					
	8103	A.	Full height cab guard. Guard to be all welded aluminum construction. Minimum 84 inches wide and 67 inches high. To include provision to hang chains and binders. Must include window (approx. 36 inches W x 18 inches H) to allow vision out of the back of the cab. East Mfg., Co. "Steel Hauler Model" Part No. 099-30105-00, Koneta "Black Max" Part No. DB 1010, Merritt "Cab Guard II" Part No. 96-1120-001 or approved equivalent. Bidder must include the cost for any additional CA dimension, if required.					
	8201	A.	Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).					
	8202	A.	Two-tone colors. Manufacturer's standard two-tone colors.					
8203	A.	Aerodynamic package. Bid to include roof air deflector and side extensions, if available.	State All Equipment Included In Bid.					
8204	A.	High back air suspension passenger seat. Bid in lieu of the matching fixed base passenger seat specified in Section 82.B.						

GROUP 6, NO. 25102100-610: TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 80,000 LBS. GCWR (6X4)

GVWR* (lbs.)⁴	52,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
ENGINE:	10	A.	Diesel engine, wet sleeve, 10.5L, 370 Gross HP (per the latest issue of SAE J1349), 1450 lbs.-ft. Gross Torque, 2000 governed RPM, minimum.	State Liters.				
				State Gross HP.				
				State Gross Torque.				
				State Governed RPM.				
				State Engine/Emissions Type.				
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	State Urea Tank Size (in gallons), if required.				
		C.		Standard cooling system with antifreeze.				
		D.	Dry type air cleaner with service (restriction) indicator.					
E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.							
F.	Vertical exhaust system or horizontal muffler with vertical exhaust pipe. Exhaust pipe must have a curved end or straight end protected with a rain cap.							
G.	Speed/cruise control.							
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.					
		B.	Batteries to have a minimum total of 1875 CCA @ 0 degrees F.					
TRANSMISSION:	20	A.	Manual overdrive transmission, ten (10)-forward speeds minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 14.56:1.					
		B.	Transmission shall be filled with synthetic lubricant.					
		C.	Minimum 15.5 inches two (2)-plate ceramic-faced clutch.					
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 12,000 lbs. capacity.					
		B.	Front shock absorbers.					
		C.	Front wheel oil-lubricated bearings and seals.					
		D.	Single speed tandem drive rear axle, minimum 40,000 lbs. capacity. Rear axle ratio is to be a 4.63 or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Minimum 40,000 lbs. rear suspension with minimum 52 inch steel walking beams. Hendrickson RT2-400/RT-403, or Approved Equivalent.	State Rear Suspension Capacity (lbs.).				
				State Rear Suspension Type.				
				State Rear Axle Ratio.				
E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.	State Top Speed (MPH).						

GROUP 6, NO. 25102100-610: TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 80,000 LBS. GCWR (6X4)

GVWR* (lbs.)⁴	52,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.					
		B.	Power steering.					
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with two speakers and antenna.					
		B.	Air conditioner with integral heater and defroster.					
		C.	Arm rests both sides, if available; sun visors, both sides.					
		D.	Tinted glass all windows, including windshield.					
SAFETY ITEMS:	60	A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.					
		B.	Standard electric horn.					
		C.	Outside mirrors, left and right side. Mirrors to be six (6) x twelve (12) inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.					
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.					
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.					
		F.	All access steps shall be self-cleaning slip-resistant grating.					
		G.	Daytime running lights.					
		H.	Rear quarter fenders, plastic, rubber or stainless steel. Factory or dealer installed. NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON FENDERS.					
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.					
		B.	Spring applied parking brake.					
		C.	Front and rear automatic slack adjusters.					
		D.	Front and rear dust shields.					
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)					
		F.	Low air pressure warning indicator.					
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	State Air Dryer with Heater Type.				
TIRES & WHEELS:	70	A.	Ten (10) 275/80R22.5G (14PR) or 295/75R22.5G (14 PR) or larger, tubeless, low profile radial tires with highway tread.					
		B.	All wheels to be one-piece steel disc, ten (10)-hole, I.S.O. hub pilot mount, 22.5 inch diameter.					
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.					

GROUP 6, NO. 25102100-610: TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 80,000 LBS. GCWR (6X4)

GVWR* (lbs.)⁴	52,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
CHASSIS, FRAME, CAB:	80	A.	Minimum 52,000 lbs. GVWR, 80,000 lbs. GCWR, factory certified.	State GVWR lbs.				
		B.	Minimum 1,800,000 in-lbs. RBM to rear end of frame, factory reinforced if necessary.	State Frame RBM in lbs.				
		C.	Cab-to-axle dimension of 96 - 102 inches minimum. NOTE TO RESPONDENT: IF MORE CAB-TO-AXLE DIMENSION IS REQUIRED TO PROVIDE THE CORRECT TRAILER SWING CLEARANCE, RESPONDENT MUST NOT PROVIDE ANY MORE THAN REQUIRED. NOTE: PURCHASER MUST PROVIDE THE CONTRACTOR WITH THE OVERALL WIDTH OF THE FRONT OF THE TRAILER AND THE KINGPIN LOCATION - DISTANCE FROM THE FRONT OF THE TRAILER TO THE KINGPIN.	State Cab/Axle dimension.				
		D.	Factory installed fuel tank(s), minimum 150 U.S. gallons.	State Fuel Tanks(s) Capacity.				
		E.	Front tow hooks or tow pins.					
		F.	Standard front bumper.					
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.	State BBC (Front bumper to back of cab) dimension.				
		B.	High back air suspension driver seat with matching fixed base companion seat.					
		C.	Grab handle(s) for cab entry, located at each entry door.					
		D.	Manufacturer's standard paint and colors.					
		E.	Rear cab window with fixed tinted glass.					
TRACTOR ITEMS:	84	A.	Air operated cab-controlled, adjustable fifth wheel. Fifth wheel shall have a slide travel length of twenty-four (24) inches. Simplex II, Holland FW 35 slider, Fontaine SL7ATB, or Approved Equivalent. Factory or dealer installed. Fifth wheel height (unloaded) must range from forty-eight (48) inches minimum to fifty (50) inches maximum. Specified height is the distance from the ground to the top of the fifth wheel.	State Manufacturer.				
				State Model No.				
				State Fifth Wheel Height (unloaded).				
				State Slide Travel Length.				
		B.	Hand controlled trailer brake connection and double check breakaway valves.					
C.	Minimum twelve (12) foot coiled tractor/trailer brake hoses with hanger.							
D.	Minimum twelve (12) foot coiled tractor/trailer seven wire light cable with adapter plug.							

GROUP 6, NO. 25102100-610: TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 80,000 LBS. GCWR (6X4)

GVWR* (lbs.)⁴	52,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
		E.	Heavy-duty aluminum fifth wheel safety platform, minimum twenty-four (24) inches in length. Factory or dealer installed.					
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/ Customer/ Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.					
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.					
		C.	Paint numbers are referenced only to identify colors.					
OPTIONS:	1010	A.	CUMMINS: 10.8L, 370 GROSS HP, 1450 lbs.-ft. Gross Torque, minimum. Bid in lieu of engine provided in the base truck. Bid "STD" if this engine was provided as the base engine. All other requirements of Section 10 apply.					
	1011	A.	DETROIT: 12.7L, 375 Gross HP, 1450 lbs.-ft. Gross Torque, minimum. Bid in lieu of engine provided in the base truck. Bid "STD" if this engine was provided as the base engine. All other requirements in Section 10 apply.					
	1012	A.	MERCEDES-BENZ: 12.8L, 370 Gross HP, 1450 lbs.-ft. Gross Torque, minimum. Bid in lieu of engine provided in the base truck. Bid "STD" if this engine was provided as the base engine. All other requirements of Section 10 apply.					
	2001	A.	Power take-off (PTO) with a SAE standard, keyed output shaft, installed. To include a dash mounted electric-over-air switch and indicator light. Chelsea 230, Muncie CS Series, or Approved Equivalent. For manual transmission only.					
	2002	A.	"Hot Shift" power take-off (PTO) with a SAE standard, keyed output shaft, installed. To include a dash mounted electric-over-hydraulic switch and indicator light. Chelsea 276, Muncie CS Series, or Approved Equivalent. USE WITH AUTOMATIC TRANSMISSION, OPTIONS 2004 AND 2005 ONLY.					
	2003	A.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.					

GROUP 6, NO. 25102100-610: TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 80,000 LBS. GCWR (6X4)

GVWR* (lbs.)⁴	52,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
	2004	A.	Automatic transmission, six (6)-speed minimum, with provisions for a PTO. Transmission to be an Allison 4500RDS, or Approved Equivalent. Bid in lieu of the base transmission. Rear axle ratio is to be a 5.43/5.63 or the closest possible ratio available that will provide a top speed of approximately 65 MPH. NOTE: FOR SUBSTANTIAL OFF ROAD USE, LOOSE DRY SAND, AND SPONGY SOIL OR LOOSE GRAVEL.	State Rear Axle Ratio.				
				State Engine RPM.				
				State Top Speed (MPH).				
	2005	A.	Automatic transmission, six (6)-speed minimum, with provisions for a PTO. Transmission to be an Allison 4000RDS, or Approved Equivalent. Bid in lieu of the base transmission. Rear axle ratio is to be a 5.43/5.63 or the closest possible ratio available that will provide a top speed of approximately 65 MPH. RECOMMENDED FOR HIGHWAY USE, PACKED SOIL, CLAY OR GRAVEL ROADS.	State Rear Axle Ratio.				
				State Engine RPM.				
				State Top Speed (MPH).				
3001	A.	"No-Spin" or driver control traction differential (DCDL) on rearmost axle or both rear axles.						
5001	A.	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.						
6001	A.	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately thirty-six (36) inches in length located on the left and right front corners of the vehicle.)						
6201	A.	Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable. See section 3.2.						
7001	A.	Tubeless radial tires with on/off highway tread for rear only. Bid eight (8) 11R22.5G (14PR) or larger tires for on/off highway use and two (2) 11R22.5G (14PR) or larger tires for on highway use. Bid in lieu of base tires. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.						
8101	A.	30,000 lb. Line pull single-speed reversible mechanical winch, PTO operated, cab-controlled. Bid to include a six (6) inch swivel safety hook and 150 feet of 3/4 inch IWRC 6x37 flexible wire rope, PTO, and all necessary controls. Braden Model AMS 10, Tulsa Model 34, or Approved Equivalent. Unit is to be mounted aft of the cab and so located as to not interfere with fifth wheel or other equipment. Bidder must include the cost for any additional CA dimension, if required. FOR USE WITH MANUAL TRANSMISSION ONLY.						

GROUP 6, NO. 25102100-610: TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 80,000 LBS. GCWR (6X4)

GVWR* (lbs.)⁴	52,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
	8102	A.	45,000 lb. Line pull variable-speed hydraulic winch. Bid to include a six (6) inch swivel safety hook, and 150 feet of 7/8 inch IWRC 6x37 flexible wire rope, PTO, adapters, direct mount hydraulic pump, valve(s) and all necessary lines and fittings. Braden Model AMS 20, Tulsa Model H64, or Approved Equivalent. Unit is to be mounted aft of the cab and so located as to not interfere with fifth wheel or other equipment. Bidder must include the cost for any additional CA dimension, if required. FOR USE WITH MANUAL OR AUTOMATIC TRANSMISSION.					
	8103	A.	Full height cab guard. Guard to be all welded aluminum construction. Minimum 84 inches wide and 67 inches high. To include provision to hang chains and binders. Must include window (approx. 36 inches W x 18 inches H) to allow vision out of the back of the cab. East Mfg., Co. "Steel Hauler Model" Part No. 099-30105-00, Koneta "Black Max" Part No. DB 1010, Merritt "Cab Guard II" Part No. 96-1120-001, or Approved Equivalent. Bidder must include the cost for any additional CA dimension, if required.					
	8201	A.	Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).					
	8202	A.	Two-tone colors. Manufacturer's standard two-tone colors.					
	8203	A.	Aerodynamic package. Bid to include roof air deflector and side extensions, if available.	State All Equipment Included In Bid.				
	8204	A.	High back air suspension passenger seat. Bid in lieu of the matching fixed base passenger seat specified in Section 82.B.					

GROUP 6, NO. 25102100-620:TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 120,000 LBS. GCWR (6X4)

GVWR* (lbs.)⁴	120,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
ENGINE:	10	A.	Diesel engine, wet sleeve, 14.0L, 435 Gross HP (per the latest issue of SAE J1349), 1650 lbs.-ft. Gross Torque, 2000 governed RPM, minimum.	State Liters.				
				State Gross HP.				
				State Gross Torque.				
				State Governed RPM.				
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	State Engine/Emissions Type.				
				State Urea Tank Size (in gallons), if required.				
		C.	Standard cooling system with antifreeze.					
D.	Dry type air cleaner with service (restriction) indicator.							
E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.							
F.	Vertical exhaust system or horizontal muffler with vertical exhaust pipe. Exhaust pipe must have a curved end or straight end protected with a rain cap.							
G.	Speed/cruise control.							
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.					
		B.	Batteries to have a minimum total of 1875 CCA @ 0 degrees F.					
TRANSMISSION:	20	A.	Manual overdrive transmission, ten (10) forward speeds minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 14.56:1.					
		B.	Transmission shall be filled with synthetic lubricant.					
		C.	Minimum 15.5 inches two (2)-plate ceramic-faced clutch.					
		D.	Transmission oil cooler.					
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 12,000 lbs. capacity.					
		B.	Front shock absorbers.					
		C.	Front wheel oil-lubricated bearings and seals.					
		D.	Single speed tandem drive rear axle, minimum 46,000 lbs. capacity. Rear axle ratio is to be a 4.56 or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Minimum 46,000 lbs. rear suspension with minimum 54 inch steel walking beams. Hendrickson RT2-460/RT-463, or Approved Equivalent.	State Rear Suspension Capacity (lbs.).				
				State Rear Suspension Type.				
	State Rear Axle Ratio.							
E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.	State Top Speed (MPH).						

GROUP 6, NO. 25102100-620:TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 120,000 LBS. GCWR (6X4)

GVWR* (lbs.)⁴	120,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.					
		B.	Power steering.					
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with two speakers and antenna.					
		B.	Air conditioner with integral heater and defroster.					
		C.	Arm rests both sides, if available; sun visors, both sides.					
		D.	Tinted glass all windows, including windshield.					
SAFETY ITEMS:	60	A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.					
		B.	Standard electric horn.					
		C.	Outside mirrors, left and right side. Mirrors to be six (6) x twelve (12) inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.					
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.					
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.					
		F.	All access steps shall be self-cleaning slip-resistant grating.					
		G.	Daytime running lights.					
		H.	Rear quarter fenders, plastic, rubber or stainless steel. Factory or dealer installed. NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON FENDERS.					
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.					
		B.	Spring applied parking brake.					
		C.	Front and rear automatic slack adjusters.					
		D.	Front and rear dust shields.					
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)					
		F.	Low air pressure warning indicator.					
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	State Air Dryer with Heater Type.				
TIRES & WHEELS:	70	A.	Ten (10) 11R22.5H (16PR) or larger tubeless radial tires with highway tread.					
		B.	All wheels to be one-piece steel disc, ten (10)-hole, I.S.O. hub pilot mount, 22.5 inch diameter.					
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.					

GROUP 6, NO. 25102100-620:TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 120,000 LBS. GCWR (6X4)

GVWR* (lbs.)⁴	120,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
CHASSIS, FRAME, CAB:	80	A.	Minimum 58,000 lbs. GVWR, 120,000 lbs. GCWR, factory certified.	State GVWR lbs.				
		B.	Minimum 2,700,000 in-lbs. RBM to rear end of frame, factory reinforced if necessary.	State Frame RBM in lbs.				
		C.	Cab-to-axle dimension 96 - 102 inches minimum. NOTE TO RESPONDENT: IF MORE CAB-TO-AXLE DIMENSION IS REQUIRED TO PROVIDE THE CORRECT TRAILER SWING CLEARANCE, RESPONDENT MUST NOT PROVIDE ANY MORE THAN REQUIRED.	State Cab/Axle dimension.				
			NOTE: PURCHASER MUST PROVIDE THE CONTRACTOR WITH THE OVERALL WIDTH OF THE FRONT OF THE TRAILER AND THE KINGPIN LOCATION - DISTANCE FROM THE FRONT OF THE TRAILER TO THE KINGPIN.					
		D.	Factory installed fuel tank(s), minimum 150 U.S. gallons.	State Fuel Tanks(s) Capacity.				
		E.	Front tow hooks or tow pins.					
F.	Standard front bumper.							
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.					
		B.	High back air suspension driver seat with matching fixed base companion seat.					
		C.	Grab handle(s) for cab entry, located at each entry door.					
		D.	Manufacturer's standard paint and colors.					
		E.	Rear cab window with fixed tinted glass.					
TRACTOR ITEMS:	84	A.	Air operated cab-controlled, adjustable fifth wheel. Fifth wheel shall have a slide travel length of twenty-four (24) inches. Simplex II, Holland FW2570 slider, Fontaine SLHAWB 24", or Approved Equivalent. Factory or dealer installed. Fifth wheel height (unloaded) must range from forty-eight (48) inches minimum to fifty (50) inches maximum. Specified height is the distance from the ground to the top of the fifth wheel. Specified height is the distance from the ground to the top of the fifth wheel.	State Manufacturer.				
				State Model No.				
				State Fifth Wheel Height (unloaded).				
				State Slide Travel Length.				
		B.	Hand controlled trailer brake connection and double check breakaway valves.					
C.	Minimum twelve (12) foot coiled tractor/trailer brake hoses with hanger.							
D.	Minimum twelve (12) foot coiled tractor/trailer seven wire light cable with adapter plug.							

GROUP 6, NO. 25102100-620:TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 120,000 LBS. GCWR (6X4)

GVWR* (lbs.)⁴	120,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
		E.	Heavy-duty aluminum fifth wheel safety platform, minimum twenty-four (24) inches in length. Factory or dealer installed.					
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Customr/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.					
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.					
		C.	Paint numbers are referenced only to identify colors.					
	1010	A.	CUMMINS: 14.9L, 450 Gross HP, 1650 lbs.-ft. Gross Torque, minimum. Bid in lieu of engine provided in the base truck. Bid "STD" if this engine was provided as the base engine. All other requirements of Section 10 apply.					
	1011	A.	DETROIT: 14.0L, 435 Gross HP, 1650 lbs.-ft. Gross Torque, minimum. Bid in lieu of engine provided in the base truck. Bid "STD" if this engine was provided as the base engine. All other requirements of Section 10 apply.					
	2001	A.	Power take-off (PTO) with a SAE standard, keyed output shaft, installed. To include a dash mounted electric-over-air switch and indicator light. Chelsea 230, Muncie CS Series, or Approved Equivalent. For manual transmission only.					
	2003	A.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.					
	3001	A.	"No-Spin" or driver control traction differential (DCDL) on rearmost axle or both rear axles.					
	5001	A.	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.					
	6001	A.	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately thirty-six (36) inches in length located on the left and right front corners of the vehicle.)					
	6201	A.	Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable. See section 3.2.					
	7001	A.	Tubeless radial tires with on/off highway tread for rear only. Bid eight (8) 11R22.5H (16PR) or larger tires for on/off highway use. Bid in lieu of base rear tires. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.					

GROUP 6, NO. 25102100-620:TRUCK TRACTOR, TANDEM AXLE, CLASS 8, 120,000 LBS. GCWR (6X4)

GVWR* (lbs.)⁴	120,000				
Intended Use:	TOWING A FIFTH WHEEL TYPE SEMI TRAILER AND TRANSPORTING UP TO TWO (2) INDIVIDUALS.				
Bidder Name:⁷	<Insert Bidder Name>	Representative Model:⁹	Rep. Model Number:¹⁰	BV Price:¹¹	OEM Options Discount:¹³
		0	0	\$ -	0.0%

Note: This detailed specification is not complete unless it is used in conjunction with all conditions of the Technical Specifications.

Specification Category: ¹⁶	Section: ¹⁷	Sub-Section: ¹⁸	Base Vehicle Specification: ¹⁹	Representative Model Specification: ²⁰	Options Specification Information: ²¹			
					MFR.: ²²	MODEL NO.: ²³	CODE/ CA Code: ²⁵	PRICE: ²⁶
OPTIONS:	8101	A.	30,000 lb. Line pull single-speed reversible mechanical winch, PTO operated, cab-controlled. Bid to include a six (6) inch swivel safety hook and 150 feet of 3/4 inch IWRC 6x37 flexible wire rope, PTO, and all necessary controls. Braden Model AMS 10, Tulsa Model 34, or Approved Equivalent. Unit is to be mounted aft of the cab and so located as to not interfere with fifth wheel or other equipment. Bidder must include the cost for any additional CA dimension, if required.					
	8102	A.	45,000 lb. Line pull variable-speed hydraulic winch. Bid to include a six (6) inch swivel safety hook, and 150 feet of 7/8 inch IWRC 6x37 flexible wire rope, PTO, adapters, direct mount hydraulic pump, valve(s) and all necessary lines and fittings. Braden Model AMS 20, Tulsa Model H64, or Approved Equivalent. Unit is to be mounted aft of the cab and so located as to not interfere with fifth wheel or other equipment. Bidder must include the cost for any additional CA dimension, if required.					
	8103	A.	Full height cab guard. Guard to be all welded aluminum construction. Minimum 84 inches wide and 67 inches high. To include provision to hang chains and binders. Must include window (approx. 36 inches W x 18 inches H) to allow vision out of the back of the cab. East Mfg., Co. "Steel Hauler Model" Part No. 099-30105-00, Koneta "Black Max" Part No. DB 1010, Merritt "Cab Guard II" Part No. 96-1120-001, or Approved Equivalent. Bidder must include the cost for any additional CA dimension, if required.					
	8201	A.	Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).					
	8202	A.	Two-tone colors. Manufacturer's standard two-tone colors.					
	8203	A.	Aerodynamic package. Bid to include roof air deflector and side extensions, if available.	State All Equipment Included In Bid.				
	8204	A.	High back air suspension passenger seat. Bid in lieu of the matching fixed base passenger seat specified in Section 82.B.					